

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Identification

Product form : Mixture  
 Product name : Eco-burner Fuel

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For use ONLY in re-fill of Ecoburner Chafo, as directed by Ecoburner Ltd. Directions for use provided in "Ecoburner Quick Start Guide." Use only with approved Ecoburner Chafo Devices.  
 Use of the substance/mixture : Fuel

### 1.3. Details of the supplier of the safety data sheet

Ecoburner, Ltd.  
 Unit 5 Airside, Gulf Stream Avenue  
 Airport Business Park  
 Waterford,  
 T +353 (0)51 353806 - F +353 (0)51 364067  
[info@ecoburner.com](mailto:info@ecoburner.com) - [www.ecoburner.com](http://www.ecoburner.com)

Table Direct  
 24 Harries Road  
 Coorparoo, QLD 4151, Australia  
 T +1300 822 533  
[www.tabledirect.com.au](http://www.tabledirect.com.au)

### 1.4. Emergency telephone number

Emergency number: NCEC Carechem Australia: +61 2 8014 4558  
 New Zealand: +64 9 929 1483

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS classification

Flam. Aerosol 1 H222 - Extremely flammable aerosol  
 Compressed gas H280 - Contains gas under pressure; may explode if heated  
 Full text of H-statements: see section 16

### 2.2. Label elements

#### GHS labelling

Hazard pictograms (GHS) :



GHS02

GHS04

Signal word (GHS) : Danger  
 Hazard statements (GHS) : H222 - Extremely flammable aerosol  
 H280 - Contains gas under pressure; may explode if heated  
 Precautionary statements (GHS) : P210 - Keep away from heat, open flames, sparks. - No smoking  
 P211 - Do not spray on an open flame or other ignition source  
 P251 - Pressurized container: Do not pierce or burn, even after use  
 P410+P403 - Protect from sunlight. Store in a well-ventilated place  
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

# Eco-burner Fuel

## Safety Data Sheet

according to Safework Australia

### 3.2. Mixture

Name	Product identifier	%	GHS classification
n-Butane	(CAS No) 106-97-8	70 – 90	Flam. Gas 1, H220
Propane	(CAS No) 74-98-6	10 – 30	Flam. Gas 1, H220
Isobutane	(CAS No) 75-28-5	1 – 5	Flam. Gas 1, H220

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Artificial respiration and/or oxygen if necessary. Call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Thaw frosted parts with lukewarm water. Do not rub affected area. Get medical advice/attention.
First-aid measures after eye contact	: Direct contact with the eyes is likely to be irritating.
First-aid measures after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: In high concentrations : Anesthetic effects. Shortness of breath. Inhalation of vapours may cause respiratory irritation. Headache. Dizziness. Nausea.
Symptoms/injuries after skin contact	: May cause moderate irritation. Rapid evaporation of the liquid may cause frostbite.
Symptoms/injuries after eye contact	: This gas is non-irritating; but direct contact with liquefied/pressurized gas or frost particles may produce severe and possibly permanent eye damage from freeze burns.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. Dry chemical. Foam. Water spray. Water fog.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity	: No dangerous reactions known.

### 5.3. Advice for firefighters

Precautionary measures fire	: Stop leak if safe to do so.
Firefighting instructions	: DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.
------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------

#### 6.1.1. For non-emergency personnel

Protective equipment	: Do not breathe aerosol. Refer to section 8.2.
Emergency procedures	: Stop leak, if possible without risk. Keep upwind. Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Do not breathe aerosol. Refer to section 8.2.
Emergency procedures	: Stop leak if safe to do so. Eliminate every possible source of ignition. Evacuate unnecessary personnel. Keep upwind.

### 6.2. Environmental precautions

Notify authorities if product enters sewers or public waters. Do not discharge into drains or the environment.

# Eco-burner Fuel

## Safety Data Sheet

according to Safework Australia

### 6.3. Methods and material for containment and cleaning up

For containment : Eliminate all ignition sources.  
Methods for cleaning up : Notify environmental authorities.

### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable. Pressurized container: Do not pierce or burn, even after use.  
Precautions for safe handling : Do not spray on an open flame or other ignition source.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Avoid static electricity discharges. No flames, no sparks. Eliminate all sources of ignition.  
Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.  
Incompatible materials : Heat sources. Direct sunlight.  
Storage area : Store in dry, cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

n-Butane (106-97-8)		
Australia	TWA (ppm)	800 ppm
Australia	TWA (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>

### 8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.  
Personal protective equipment : Avoid all unnecessary exposure. Accidental release of the contents: avoid leaks.  
Hand protection : None under normal use. It is a good industrial hygiene practice to minimize skin contact. In case of repeated or prolonged contact wear gloves. Insulated gloves.  
Eye protection : None under normal use. In case of splashing or aerosol production: protective goggles.  
Respiratory protection : No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation. In case of inadequate ventilation wear respiratory protection. Use self-contained breathing apparatus.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas  
Appearance : Aerosol.  
Colour : Colourless  
Odour : Sweet petroleum  
Odour threshold : No data available  
pH : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : -42.2 - -0.5 °C (-1.1 - 31.1 °F)  
Flash point : -104.4 °C (-156 °F (estimated))  
Relative evaporation rate (butyl acetate=1) : No data available  
Relative evaporation rate (ether=1) : > 1  
Flammability (solid, gas) : No data available  
Explosive limits : No data available  
Explosive properties : No data available  
Oxidising properties : No data available  
Vapour pressure : 40 PSIG @ 70 °F

# Eco-burner Fuel

## Safety Data Sheet

according to Safework Australia

---

Relative density	: 0.567
Relative vapour density at 20 °C	: 1.886
Solubility	: Water: 0.008 % @ 70 °F
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: 0.084 - 0.14 cP liquid
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

### 9.2. Other information

VOC content	: 100 %
-------------	---------

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame. Direct sunlight. Overheating.

### 10.5. Incompatible materials

Strong oxidizers. Alkali. Strong mineral acids.

### 10.6. Hazardous decomposition products

Carbon monoxide. Mixture of hydrocarbons.

---

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure	: Inhalation; Skin and eye contact
Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: In high concentrations : Anesthetic effects. Shortness of breath. Inhalation of vapours may cause respiratory irritation. Headache. Dizziness. Nausea.
Symptoms/injuries after skin contact	: May cause moderate irritation. Rapid evaporation of the liquid may cause frostbite.
Symptoms/injuries after eye contact	: This gas is non-irritating; but direct contact with liquefied/pressurized gas or frost particles may produce severe and possibly permanent eye damage from freeze burns.

---

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

# Eco-burner Fuel

## Safety Data Sheet

according to Safework Australia

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Container under pressure. Do not drill or burn even after use. Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

### Australia Dangerous Goods (ADG) Code

In accordance with ADG

UN-No. : UN1950  
Proper Shipping Name : AEROSOLS  
Transport hazard class(es) : 2 - Class 2  
Hazard labels : 2 - Flammable gas



Special Provisions : 63  
190  
277  
327  
344  
Limited Quantities : See SP 277  
Packagings & IBCs Packing Instruction : P207  
LP02  
Packagings & IBCs Special Packing Provisions : PP87  
L2

### Transport by sea

UN-No. (IMDG) : 1950  
Proper Shipping Name (IMDG) : AEROSOLS  
Class (IMDG) : 2 - Gases

### Air transport

UN-No. (IATA) : 1950  
Proper Shipping Name (IATA) : Aerosols, flammable  
Class (IATA) : 2

## SECTION 15: Regulatory information

### National regulations

#### n-Butane (106-97-8)

Listed on the AICS (Australian Inventory of Chemical Substances)

#### Isobutane (75-28-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

#### Propane (74-98-6)

Listed on the AICS (Australian Inventory of Chemical Substances)

# Eco-burner Fuel

## Safety Data Sheet

according to Safework Australia

### SECTION 16: Other information

- Indication of changes : Section 2 information (other than label requirements)
- Revision date : 12/23/2015
- Data sources : Australia Worksafe "Preparation of Safety Data Sheets for Hazardous Chemicals".  
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.  
Kristen Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.  
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
- Abbreviations and acronyms : CAS (Chemical Abstracts Service) number.  
ATE: Acute Toxicity Estimate.  
CLP: Classification, Labelling, Packaging.  
EC50: Environmental Concentration associated with a response by 50% of the test population.  
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).  
LD50: Lethal Dose for 50% of the test population.  
NOEC: No Observable Effect Concentration.  
OSHA: Occupational Safety & Health Administration.  
PNEC: Predicted No Effect Level.  
STEL: Short Term Exposure Limits.  
TSCA: Toxic Substances Control Act.  
TWA: Time Weight Average.
- Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

#### Full text of H-statements:

Compressed gas	Gases under pressure : Compressed gas
Flam. Aerosol 1	Flammable aerosols, Category 1
Flam. Gas 1	Flammable gases, Category 1
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated

Redstone SDS AUS GHS for Ecoburner

**SDS Prepared by:** The Redstone Group, LLC.  
6077 Frantz Rd.  
Suite 206  
Dublin, Ohio USA 43016  
614.923.7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*